





www.joinset.com

2015

Electronic

Materials Components

SMD Shield Clip

- ¬ Shield Clip
- — Shield Clip







Joinset Co., Ltd.

9B-51L, Panwol Industrial Complex, Haean-ro, Danwon-gu, Ansan-city Kyunggi-Do KOREA

Tel.) 82-31-495-2601 [REF] Fax) 82-31-495-2693

- Please contact a person in charge for detail
- Technical Inquiry: Tommy Lee, lsi@joinset.com



SMD Shield Clip



Easy Re-Work

Easy Installation

1 SMD Shield Clip?

"SMD Shield Clip" is the metal clip for Shield Case(Can) that is used for the EMI shielding.

"SMD Shield Clip" is mounted on the ground pattern of PCB by reflow soldering of SMT, then Shield Case will be inserted into the "SMD Shield Clip".

You can remove the Shield Case from "SMD Shield Clip" for rework.


There are two shapes of "SMD Shield Clip", one is "—" shape for standard usage and the other is " ¬ " shape for rectangular usage. " ¬ " shape "SMD Shield Clip" can provide the best insertion condition and can reduce the number of "SMD Shield Clip" comparing with "—" shape. The height of outer wing of " ¬ " shape of "SMD Shield Clip" is higher than its height of inner wing for easy insertion of Shield Case.

2 FEATURES


- Suitable for easy re-work
 * Proper insertion & withdrawal force
- Meet EU-RoHS, Halogen Free, Beryllium Free
- " ¬ " shape can reduce the number of Clips (cost & size save)


3 Applications

Mobile phone, Navigation, TV, PDA, Internet Repeater, RF Controller, etc.











Walkie-Talkie






4 Shape and Kinds





4 Shape and Kinds




5 Properties

Item	SC-080-01	SC-080-90	SC-128-01	SC-128-90	SC-200-01	SC-350-01			
Material	Stainless Steel								
Finish	Tin Plated								
Thickness	0.15mm 0.10mm					0.2mm			
Thick. Of Shield Can	0.15~	0.20 ^{mm}		0.2-0.25 ^{mm}					
Operating Temp.	-25℃ ~ 150℃								
Resistance	Max 100mΩ								
Solderability	More than 95%								
Insertion Force	Max 2.0kgf					Max 1.5kgf			
Withdraw at Force	Min. 0.05kgf					Min 0.03kgf			
Number of Insertion Repetition	Max. 10 times								
Environment	Eu-RoHS Compliant, Pb & Halogen Free								
Thickness of Solder Cream(Recommend)	0.08mm ~ 0.12mm								



6 Shield Case's Recess Area for insert insertion of Shield Clip



7 Product Name(How to Order)

① Serial	Shield Clip						
② Height(mm)	Product Height						
	01:"一" Type	90 : "¬" Type					
③ Туре	Wight(M) (Height(H))	Length(L)					

Produ	ct Name	SC-080-01	SC-080-90	SC-128-01	SC-128-90	SC-200-01	SC-350-01
Packing Quantity	Reel	20,000ea	6,000ea	15,000ea	6,000ea	5,000ea	1,500ea
	Вох	220,000ea	66,000ea	135,000ea	54,000ea	45,000ea	21,000ea